CONTACT

DELTA JS AG

Technoparkstrasse 1 CH - 8005 Zürich Switzerland

Phone: ++41 44 445 3130 Fax: ++41 44 445 3139 E-mail: contact@delta-js.ch Homepage: www.delta-js.ch



DELTA JS AG

Machine Dynamics Engineering * Consulting * Software





Machine Dynamics Engineering * Consulting * Software



MADYN 2000

Software for General Rotordynamics



UNIQUE MODELLING CAPABILITIES

- Rotor gear bearing systems for torsional, lateral, axial and coupled analyses
- Parallel shafts gears and planetary gears with stationary as well as rotating planet carriers
- Consideration of the lateral, torsional and axial coupling in gears
- Bearing types: Spring and damper, linear & nonlinear rolling element bearings, linear & nonlinear fluid film bearings and floating ring bearings, magnetic bearings (radial and axial)
- Rolling element bearings are considered with a 5x5 stiffness matrix taking into account the lateral and rotational stiffness about bending axes and the lateral, axial coupling.
- For fluid film bearings various effects can be considered: 2-phase flow in cavitation zones taking into account ambient pressure, turbulence, different oil supply conditions and axial sealing, thermoelastic deformation, canting
- Tilting pad bearings with frequency dependent characteristic
- Magnetic bearing controllers can be modelled by proven controller building blocks similar to real systems.
- Bearing supports (casings and foundations): Spring mass damper, coupled



Model of a steam turbine generator train with planetary gear



Machine Dynamics Engineering • Consulting • Software

Your global partner for rotordynamics.

transfer functions (couplings between different bearings are considered), state space matrices

- General spring (6x6 full stiffness and damper matrix)
- Flexible couplings with linear and nonlinear characteristics
- Fluids (for seal effects) with speed dependent coefficients
- Elastic mounting of masses with an axial offset to their centre of gravity
- Superimposed shaft sections with different materials
- Temperature dependent materials
- Import of rotor data from text files via a flexible interface
- Active system for torsion allows modelling linear relations by state space matrices between torsional deflections and velocities and torques
- For further user specific modelling custom blocks can be defined.
- Mechanisms causing hot spots (e.g. Morton effect)
- User defined nonlinearities (apart from the standard nonlinearities for fluidfilm bearings and flexible couplings) can be defined with the help of custom blocks and MATLAB code.

Model of a pump with inner and outer rotor

2/3

POWERFUL ANALYTICAL CAPABILITIES

- Static analyses: Force, gear, weight loads, misalignment (optional consideration of journal position in fluid films and the deformation in rolling element bearings), alignment optimization for force free coupling
- Damped eigenvalues: Complete systems are considered, e.g. consisting of the rotor, a magnetic bearing system and a stator system (casings and foundations), i.e. no interative solution for frequency dependent characteristics.
- Harmonic response to unbalance, forces and moments, base acceleration
- Linear and nonlinear transient response to forces and moments, base acceleration

- Linear and nonlinear transient run ups and downs
- Parameter variation (eigenvalues as a function of a parameter): Undamped critical speed map, Campbell diagram (speed variation), bearing stiffness and damping variation, flexible coupling stiffness variation, general parameter variation
- Hot spot stability, among others Morton effect stability
- Optimization of magnetic bearing controller parameters with respect to damping, bearing forces and robustness
- Alignment optimization considering the oil film

EASY TO USE GRAPHICAL USER INTERFACES (GUIS)

- to model,
- to apply loads,
- to define and start analyses,
- to select and present results.
- The system explorer allows controlling every step of a rotor dynamic analysis: Modelling, defining loads and analysis parameters, viewing results

OBJECT ORIENTED DATA STRUCTURE

- to have self-contained objects such as bearings, shafts, gears or systems,
- for easy combination and mounting of model parts such as bearings and shafts,
- to simply create libraries by storing objects in appropriate directories.
- Consistent and complete information (model, loads, analysis parameters and results) is stored in a system. Its behaviour is intelligent to maintain consistency, i.e. in case of changes affected results are cleared.

Mode shape of a turbine generator train



Hot spot stability chart (Morton effect) with shape at lowest threshold



Spectrum of the nonlinear transient run up of a turbocharger

Rede armine Biologia armine Biologia Carlo armine Biologia Carlo armine Biologia Biologia Carlo armine Carlo	Mater Dreft	111-Speak Pro-	(25.09 Unided 36	the few fungeaux	ME		
	Point Built From 5 The Composed of the Compo	Real of the second seco				erenti Josh Josh Des Taparis Com Taparis Com Taparis	
		ror	Littel 1 Material Deviation (Sour Properties (2000) 21-125	The later (but read (bin) rel1 0.3 (bit) 0.3	ers Nels - 9 en 5 Barl	t GUI	Speed LTVI.10 9 N Second 4 Notice Loss Rates and Facts and Facts both The deates in routon in
Jystern		- tan A	TAces Dof	Shaft color			

System explorer with graphical user interfaces



Coupled lateral torsional vibration mode



Resonance curve of casing vibrations at support with shape at 3400 rpm



Campbell diagram of system with inner and outer rotor



Magnetic bearing transfer functions with eigenvalues for stability check

PLOTS OF MODELS AND RESULTS

- Plots are clear and practice oriented with complete and consistent information. Various options for the presentation of very complex information are offered (add data tips, select individual shafts ...).
- Curves of diagrams can be copied and pasted for comparison of results between different systems.
- Model plots are available at all hierarchical levels: Systems, gears, shafts, bearings, couplings.
- Shape plots (results along shaft axes) for deformations, forces and moments, stresses
- Clear presentation of time dependent shapes
- Resonance plots with various options (selectable lateral directions, main axis of orbits, relative vibration, API evaluation of resonances for lateral vibrations)
- Presentation of eigenvalues in Campbell diagrams and other diagrams with sophisticated sorting
- Various other diagrams for parameter variation results
- Plots for the time history, orbits and shapes of transient response results
- Plots can be configured by the user.

AUTOMATION OF ANALYSES

- Batch processing files can be created and imported to different systems. The use of denotations for objects allows generalizing loads and analyses parameters for various systems.
- With the help of a command line interface objects can be addressed and their properties changed using WINDOWS scripting.

SERVICES

- A standard training within a general rotor dynamic seminar takes place twice a year. Individual trainings are offered either in DELTA JS or the client's offices.
- Support by e-mail and telephone
- Maintenance with regular updates. Updates include new features and improvements to enhance the user friendliness and robustness.

HOW TO CONTACT DELTA JS:

DELTA JS AG

Technoparkstrasse 1 CH - 8005 Zürich Switzerland

Phone: ++41 44 445 3130 Fax: ++41 44 445 3139 E-mail: contact@delta-js.ch Homepage: www.delta-js.ch

6/7



Mode shape of a pump with inner and outer rotor